



## FOOD PLANTS – ALKALINE GENERAL CLEANERS

General cleaners are considered high foaming products

PRODUCT	L/P	USDA AUTH.	PH (L-1% by vol.) (P-1 oz. / gal.)	CONC (L-% by vol.) (P-oz. / gal.)	MAXIMUM USAGE TEMP. (°F.)	METAL SAFETY WHEN USED AS DIRECTED				FEATURES		
						ALUMINIUM	FERROUS	STAINLESS	ZINC	CHLORINATED	SILICATED	SOLVENCY
AQUABLU MF	L	*	11.2 – 11.6	1 – 5	150	■	■	■	■	○	●	○
AQUACLEAN	L	A1	9.8 – 10.0	3 – 25	160	■	■	■	■	○	●	●
AQUACLEAN PLUS	L	A1	10.5 – 10.7	3 – 25	160	■	■	■	■	○	●	●
CLEANZIT	L	*	10.3 – 10.7	3 – 10	120	□	■	■	□	○	○	●
CLEANZIT N	L	*	9.0 – 9.5	3 – 10	120	■	■	■	■	○	○	●
COMPOUND HS-30	L	A1	12.3 – 12.8	1 – 5	140	-	■	■	-	○	○	○
COMPOUND 14-XP	L	A1	11.1 – 11.3	1 – 5	140	■	■	■	■	●	○	○
DART 351	L	A1	12.0 – 12.3	1 – 10	140	■	■	■	■	○	●	●
DART 354	L	A1	11.7 – 11.8	2 – 30	180	-	■	■	-	○	●	●
DART 444	L	A1	12.2 – 12.5	2 – 10	140	□	■	■	□	●	○	○
DART 444-NP	L	*	12.2 – 12.5	2 – 10	140	□	■	■	□	●	○	○
DART 444-W	L	*	12.2 – 12.5	2 – 10	140	□	■	■	□	●	○	○
FAST CLEAN	L	A1	12.2 – 12.5	2 – 5	140	□	■	■	□	●	○	○
FAST CLEAN NC	L	*	12.3 – 12.8	2 – 5	140	□	■	■	□	○	○	○
FAST CLEAN NP	L	*	12.0 – 12.5	1 – 5	140	□	■	■	□	●	○	○
LIQUID GP	L	A1	10.0 – 10.2	5 – 20	140	-	■	■	-	○	○	●
LIQUID GP-D	L	*	8.5 – 9.5	5 – 100	140	■	■	■	■	○	○	●
MADISON CONCENTRATE	L	A4	8.5 – 8.7	1 – 10	140	■	■	■	■	○	○	●
SPECTRA BLUE	L	A1	11.4 – 12.0	3 – 10	140	■	■	■	■	○	○	●
SPECTRA PINK	L	A1	10.2 – 10.4	4 – 10	160	■	■	■	■	○	●	●

L Liquid  
P Powder  
▼ Contains SARA 313 reportables

● Applicable  
○ Non-applicable  
NP Non-phosphate (0.5% or less elemental P)

■ Safe  
□ Controlled etch  
- Rapid attack

Written data is for typical applications. Please consult your Madison Chemical Company representative for your specific application.

\* This product formulated after 63FR7319 (Federal Register), Feb. 13, 1998. For further information contact Madison Chemical Company Food Division Technical Director.

# FOOD PLANTS – ALKALINE GENERAL CLEANERS (Continued)

General cleaners are considered high foaming products

PRODUCT	L/P	USDA AUTH.	PH (L-1% by vol.) (P-1 oz. / gal.)	CONC (L-% by vol.) (P-oz. / gal.)	MAXIMUM USAGE TEMP. (°F.)	METAL SAFETY WHEN USED AS DIRECTED				FEATURES		
						ALUMINUM	FERROUS	STAINLESS	ZINC	CHLORINATED	SILICATED	SOLVENCY
SPECTRA YELLOW	L	A1	11.7 – 12.0	4 – 20	140	□	■	■	□	●	○	○
SPECTRA YELLOW HD	L	*	12.0 – 12.5	2 – 10	140	□	■	■	□	●	○	○
SPECTRA 315	L	*	8.0 – 9.0	2 – 10	140	■	■	■	■	○	○	●
COMPOUND CL-2	P	A1	11.3 – 11.5	0.5 – 4.0	140	□	■	■	□	●	○	○
COMPOUND DC-14	P	A1	11.3 – 11.6	0.5 – 4.0	140	■	■	■	■	○	●	○
COMPOUND DC-144	P	A1	11.5 – 12.0	0.5 – 4.0	140	□	■	■	□	○	●	○
COMPOUND L-14	P	A1	11.6 – 11.8	0.5 – 4.0	140	□	■	□	■	●	●	○
GENERAL PURPOSE N	P	A1	10.5 – 11.0	0.5 – 2.0	140	■	■	■	■	○	●	○
GENERAL PURPOSE O-2	P	A1	10.7 – 11.1	0.5 – 3.0	100	■	■	■	■	○	○	○

L Liquid  
P Powder  
▼ Contains SARA 313 reportables

● Applicable  
○ Non-applicable  
NP Non-phosphate (0.5% or less elemental P)

■ Safe  
□ Controlled etch  
- Rapid attack

Written data is for typical applications. Please consult your Madison Chemical Company representative for your specific application.

\* This product formulated after 63FR7319 (Federal Register), Feb. 13, 1998. For further information contact Madison Chemical Company Food Division Technical Director.